





ARCHITECTURAL CEILING TILE SLOT DIFFUSER
 SUPPLY • 24" x 24" MODULE
 MODELS: 5075 CTD-F 3/4" SLOT
 5010 CTD-F 1" SLOT

FOR "FINELINE®" TYPE AND NARROW REGRESSED T-BAR CEILINGS



MODEL TYPE:

- 5075 CTD-F 3/4" SLOT
- 5010 CTD-F 1" SLOT

NO. OF SLOTS:

- 1 SLOT 3 SLOT
- 2 SLOTS 4 SLOTS

INLET SIZE:

- 6" 10" 14"
- 8" 12"

OPTIONS:

- Internal Insulation
- External Foil Back Insulation
- SP Special Paint Finish _____

NOTES:

1. The Nailor 5000 CTD-F Series has been designed with the architect in mind to provide an unobtrusive high performance ceiling diffuser that utilizes a center ceiling tile matching the surrounding ceiling system.
2. The Nailor 'Ice Tong' Pattern Controllers are individually adjustable for each slot to provide a tight horizontal or vertical throw as well as volume control. The unit is ideally suited for use in VAV systems. Discharge patterns are fully field adjustable for 1-way, 2-way corner, 2-way opposite, 3-way or 4-way blow patterns.
3. The 5000 CTD-F Series is designed for use with "Donn Fineline" and "Chicago Ultraline 3500/3600" type narrow regressed T-bar ceiling systems.
4. MATERIAL: Extruded aluminum face with staked and welded mitered corners. Steel pattern controllers and plenum. Plenum is easily removable for installation of ceiling tile (by others).
5. FINISH: AW Appliance white with flat black pattern controllers.

FINELINE® is a registered trademark of USG Interiors Inc.

NO. OF SLOTS	CEILING TILE CUTTING DIMENSION		H DIM.
	SLOT WIDTHS (S)		
	3/4"	1"	
1	20 1/8 x 20 1/8	19 5/8 x 19 5/8	5
2	17 1/8 x 17 1/8	16 1/8 x 16 1/8	5
3	14 1/8 x 14 1/8	12 5/8 x 12 5/8	6 3/4
4	11 1/8 x 11 1/8	9 1/8 x 9 1/8	6 3/4

SCHEDULE TYPE:	
PROJECT:	
ENGINEER:	
CONTRACTOR:	

Dimensions are in inches (mm).

DATE	B SERIES	SUPERSEDES	DRAWING NO.
10 - 13 - 09	5000	31 - 8 - 00R	5000-CTDF