



UNDERFLOOR FAN BOOSTER UNIT WITH ECM MOTOR


VARIABLE OR CONSTANT VOLUME

MODELS: 38F, 38FW & 38FE • UNIT SIZES: 1, 3 & 5

STANDARD FEATURES:

- 20 ga. (1.0) galvanized steel casing components.
- Full size top access panel.
- Discharge opening designed for flanged duct connection.
- 1/2" (13) dual density insulation, exposed edges coated to prevent air erosion. Meets requirements to NFPA 90A and UL181.
- Ultra-high efficiency ECM fan motor. EPIC fan volume controller.
- Motor blower assembly mounted on special 16 ga. (1.6) angles and isolated from casing with rubber isolators.
- Single point electrical connection.
- Top access hinged door on the line voltage/fan controls enclosure.
- Controls mounted as standard on RH side as shown. Terminals ordered with LH controls (optional) are inverted and discharge duct location/elevation will therefore change.

☐ Model 38F Basic Unit



OPTIONS:

- Filter frame and 1" (25) disposable filter.
- Toggle disconnect switch.
- Fiber-free liner.
- Perforated metal liner.
- Steri-liner.
- Isolator pads.
- Fan unit fusing.
- Left hand controls location.
- Discharge collar. Flat oval for flexible duct connection.

Unit size	Collar
1	8" (9" x 5 7/8")
3	12" (14 1/4" x 7 3/4")
5	14" (17 3/8" x 7 3/4")
- Special features: _____.

Dimensional Data. Imperial Units (inches)

Unit Size	W	H	L	B	P	Q	Inlet IW x IH	Outlet Discharge DW x DH	Filter Size
1	20	8 1/2	40	1 3/8	4	3/4	17 x 5 3/4	7 1/8 x 3 3/4	19 x 7
3	20	11	40	1 3/8	2	2	17 x 8	11 1/4 x 7	19 x 10
5	20	15	44	1 1/4	2	4 3/4	17 x 12	11 3/8 x 8 1/4	20 x 15

Dimensional Data. Metric Units (mm)

Unit Size	W	H	L	B	P	Q	Inlet IW x IH	Outlet Discharge DW x DH	Filter Size
1	508	216	1016	35	102	19	432 x 146	181 x 95	483 x 178
3	508	279	1016	35	51	51	432 x 203	286 x 178	483 x 254
5	508	381	1118	32	51	121	432 x 305	289 x 210	508 x 381

Electrical Data

Unit Size	Motor H.P.	ECM Motor			
		Voltage	120/1/60	208/240/1/60	277/1/60
1	1/3	Watts	277	276	270
		FLA	3.7	1.9	1.9
3	1/3	Watts	420	450	410
		FLA	5.8	3.4	2.9
5	3/4	Watts	930	1080	940
		FLA	12.6	6.2	5.5

FLA = Full load amperage



SCHEDULE TYPE:

PROJECT:

ENGINEER:

CONTRACTOR:

Page 1 of 2.
Dimensions are in inches (mm).

DATE	B SERIES	SUPERSEDES	DRAWING NO.
3 - 9 - 09	38F	8 - 20 - 08	38F-1

**Hot Water Coil Section
Model 38FW**

Standard Features:

- Coil section installed on unit discharge.
- Coil (and header on multi-circuit units) is installed in insulated casing for increased thermal efficiency.
- 1/2" (13) copper tubes.
- Aluminum ripple fins.
- Sweat connections: One Row 1/2" (13) O.D. male solder. Two and three row 7/8" (22) O.D. male solder.
- Top access panel for inspection and coil cleaning.
- Flanged outlet duct connection.

Coil Rows:


- 1-Row 2-Row 3-Row

Coil Connections:

- (Looking in direction of airflow).
 Right hand (illustrated). Standard.
 Left hand. Optional.

Option:

- Discharge collar for flexible duct (see page 1 for dimensional data).



Unit Size	Imperial Units (inches)					Metric Units (mm)				
	Outlet Discharge C x D	H	E	J	K	Outlet Discharge C x D	H	E	J	K
1	14 3/4 x 5 3/4	8 1/2	20	1	1 3/4	375 x 146	216	508	25	44
3	14 3/4 x 8 3/4	11	20	1 1/8	1 1/8	375 x 222	278	508	29	29
5	20 x 12 1/2	15	24 3/4	1 1/2	2	508 x 318	381	629	38	51

Electric Coil Section Model 38FE

Standard Features:

- Coil installed on unit discharge.
- Insulated heater element wrapper.
- Automatic reset high limit cut-outs (one per element).
- Flanged outlet duct connection.
- Airflow safety switch to prove airflow.
- Single Point electrical connection for entire terminal unit.
- Terminal unit with heater is ETL listed as an assembly.
- Controls mounted as standard on RH side as shown.

Voltage:

Single phase, 60 Hz. 208V 240V 277V


Three phase, 60 Hz. (Unit Size 3 and 5 only)

208V 480V (4 wire wye).

_____ .

Options:

- Toggle disconnect switch.
- Door interlock disconnect switch.
- Mercury contactors.
- Power circuit fusing.
- Class 'A' 80/20 Ni./Cr. Wire.
- Dust tight construction.
- Manual reset secondary thermal cut out.
- Discharge collar for flexible duct (see page 1 for dimensional data).



Unit Size	Imperial Units (inches)						Metric Units (mm)					
	Outlet Discharge F x G	H	N	C	R	S	Outlet Discharge F x G	H	N	C	R	S
1	8 1/4 x 6	8 1/2	9	1 3/8	1	1 1/2	210 x 152	216	229	35	25	38
3	11 x 7 3/4	11	9	1	1 5/8	1 5/8	279 x 197	278	229	25	41	41
5	12 x 8 3/4	15	13 3/4	1	1	5 1/4	305 x 222	381	352	25	25	133

SCHEDULE TYPE:

PROJECT:

ENGINEER:

CONTRACTOR:

Page 2 of 2.
Dimensions are in inches (mm).

DATE

B SERIES

SUPERSEDES

DRAWING NO.

3 - 9 - 09

38F

8 - 20 - 08

38F-1